



Applications


- > UPS/EPS
- > Power systems
- > Telecommunications system
- > Emergency lighting、Auto control system
- > Solar/wind generating storage cyclic
- > Other general purpose

General Features

- > High corrosion resistant performance: Pb-Ca multi-alloy grid
- > High energy density and power density
- > Optimized capability of instant high-current discharging
- > Excellent charge acceptance ability
- > Excellent deep cycle discharge capability
- > Strong high and low temperature performance
- > Precision sealing technology



Dimension: 165L×125(W)×175(H)×175(TH) Unit: mm



Terminal Dimensions

Specification

Nominal Voltage	12V
Nominal Capacity	26.0Ah
Design life	5 years
Terminal	M6
Approx. Weight	Approx8.20kg (18.1lbs)
Container Material	ABS
Rated Capacity	26.0Ah → 20Hour Rate (1.30A to 10.5V)
	20.5Ah → 3Hour Rate (6.84A to 10.2V)
	16.3Ah → 1Hour Rate (16.3A to 9.60V)
Internal resistance	Full charged at 25°C: 16.0 mΩ
Max. Discharge Current	390A(5S)
Operating Temperature	Discharge: -20 ~50°C(-4~ 122°F)
	Charge: -20 ~50°C(-4~ 122°F)
	Storage: -20 ~50°C(-4~ 122°F)
Charge current:	Max.6.50A ; Recom.2.60A
Charge Method (25 °C)	Float Charge:13.5-13.8V,recom.13.8V(-18mV/ °C)
	Equalize charge:13.8-14.1V,recom.14.1V(-24mV/ °C)
	Cycle charge:14.4-15.0V,recom.14.7V(-30mV/ °C)
Self discharge	3% of capacity declined per month at 25°C

Constant Current Discharge Characteristics Unit: A (25°C, 77°F)


FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	85.1	66.1	45.7	26.0	20.0	16.3	10.2	9.35	7.01	4.90	4.54	3.62	2.98	2.51	1.32
1.65V	82.5	64.2	44.3	25.5	19.8	16.2	10.1	9.29	6.95	4.86	4.51	3.59	2.95	2.49	1.31
1.70V	79.2	61.2	43.5	25.0	19.7	16.1	10.0	9.21	6.84	4.81	4.46	3.55	2.93	2.47	1.31
1.75V	72.8	58.6	41.9	24.8	19.4	15.8	9.93	9.08	6.76	4.76	4.40	3.52	2.90	2.44	1.30
1.80V	65.3	55.3	39.2	23.7	18.9	15.4	9.83	8.92	6.73	4.71	4.30	3.49	2.90	2.42	1.29
1.85V	58.3	49.4	34.9	21.7	17.5	14.3	9.54	8.46	6.34	4.57	4.08	3.38	2.77	2.34	1.27

Constant Power Discharge Characteristics Unit: W/cell((25°C, 77°F)


FV/Time	5min	10min	15min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V	143	119	80.6	47.0	37.1	30.9	19.5	17.6	13.3	9.55	8.62	7.09	5.80	4.83	2.61
1.65V	137	115	79.2	46.5	36.7	30.6	19.3	17.6	13.2	9.44	8.57	7.01	5.75	4.78	2.60
1.70V	137	110	78.2	46.5	36.4	30.4	19.1	17.5	13.1	9.34	8.51	6.93	5.72	4.73	2.59
1.75V	127	106	77.9	46.3	36.1	30.1	19.0	17.4	13.0	9.28	8.46	6.89	5.69	4.70	2.58
1.80V	117	100	73.6	45.0	35.8	29.8	18.7	17.4	13.0	9.18	8.35	6.82	5.64	4.65	2.56
1.85V	104	88.9	65.8	41.3	33.2	27.7	18.4	16.6	12.3	9.02	7.98	6.70	5.45	4.57	2.54

JS12-26


Discharge characteristic




Charging characteristic




The effect of temperature on capacity




The effect of discharge depth on cycle life



Curves of self-discharge



The effect of temperature on float life



www.kijo.com.cn info@kijo.com.cn

Jiangxi Jingjiu Power Science&Technology Co. Ltd.
Add: 1388 Fushan No.1 Street, Xiaolan Economic Development Zone, Nanchang City, Jiangxi Province, China.

+86-791-85982779 +86-791-85989842

Jiangxi Jingjiu Power (Jiujiang) Co. Ltd.
Add: Xiwang Rd, Aicheng Industrial Park, Yongxiu Country, Jiujiang City, Jiangxi Province, China.

